



Certification Number
12360

Standard Version
5.0

Lead Assessment Body
Eco Intelligent Growth (EIG)

Material Health
Assessment Body
MBDC

Effective Date
25 June 2026

Expiration Date
24 June 2029

JVP S.R.L.

Viale dell'Industria n° 16/20, Piove di Sacco, Italy

has successfully achieved C2CCertified®Circularity Silver
for the product(s) under the name:

JVP 4x4 steel encapsulated with gypsum fiber core raised access floor panels

Please see the List of Certified Products (available on the Cradle to Cradle Certified Product Registry) for all products included in this certification.

The following products or variations are excluded from the certification: pedestals located on the bottom of the panel.

Elwyn Grainger-Jones
Executive Director
Cradle to Cradle Products Innovation Institute

See the Cradle to Cradle Certified Product Registry at www.c2ccertified.org for additional details
Use of the certification marks is subject to the terms and conditions of the C2CPII Certification Agreement and Trademark Use Guidelines.
Cradle to Cradle Certified is a registered trademark of the Cradle to Cradle Products Innovation Institute

Amsterdam, The Netherlands
San Francisco, California, USA



JVP 4x4 steel encapsulated with gypsum fiber core raised access floor panels

JVP S.R.L.

The following products are covered under this certification number 12360:

Product Name	Description
P3TTL000	Inert calcium sulphate and recycled paper fibers core, density 1200 kg/m ³ , encapsulated in galvanized steel sheets, thickness 0,40mm. Nominal dimensions: 600mm of length, 600mm of width, 23mm of thickness, 12,50kg of weight.
P4TTM000	Inert calcium sulphate and recycled paper fibers core, density 1200 kg/m ³ , encapsulated in galvanized steel sheets, thickness 0,40mm. Nominal dimensions: 600mm of length, 600mm of width, 29mm of thickness, 15,30kg of weight.
P4TTH000	Inert calcium sulphate and recycled paper fibers core, density 1600 kg/m ³ , encapsulated in galvanized steel sheets, thickness 0,40mm. Nominal dimensions: 600mm of length, 600mm of width, 29mm of thickness, 18,50kg of weight